

2019

dupal^{UK}

L8HS

TECHNICAL SPECIFICATION



L8HS



MATERIAL

White ABS impregnated with antibacterial additive on head.

Hose tube: White reinforced PVC with Antibacterial additive.

Hose fitting: ABS impregnated with antibacterial additive.



WORKING PRESSURE RANGE

0.5 bar – 5 bars



WORKING TEMPERATURE RANGE

Up to 75°C



FLOW RATE

8 litres per min at 2.5 bars.



APPROVALS

WRAS approval



FITTINGS

1/2" BSP female



PRODUCT MARKING

Dupal on the Shower Face (button)



COLOURS

Blue, Purple, Red and Green.
Order determined after customer consultation.



Detachable face for easy inspection and replacing.


— No tools needed

Face Kit

- Single face kits and 3 coloured faced kits are available for purchasing separately.
- Each kit is supplied with silicone seal and new silicone washers.
- The L8 HS is supplied with white coloured hose fittings as default.



dupal^{UK}



WRAS
APPROVED PRODUCT

01 342 844 844
sales@dupaluk.com
www.dupaluk.com

Dupal UK Limited
39 Careys Wood, Smmallfield
Surrey RH6 9PA, UK

VAT Number: 233 5070 38
Company Number: 09932632

dupal^{UK}