

2025

[L8] shower

# TECHNICAL SPECIFICATION



No Tools Needed

# L8 shower



## **MATERIAL**

White ABS impregnated with antibacterial additive.

Hose tube: White reinforced PVC with Antibacterial additive.

Hose fitting: ABS impregnated with antibacterial additive.



## **WORKING PRESSURE RANGE**

0.5 bar – 5 bars



## **WORKING TEMPERATURE RANGE**

Up to 75°C



## **FLOW RATE**

8 litres per min at 2.5 bars.



## **APPROVALS**

WRAS approval (Head and Hose)



## **FITTINGS**

1/2" BSP female



## **PRODUCT MARKING**

Dupal on the Shower Face (button)



## **COLOURS**

Blue, Purple, Red and Green.  
Order determined after customer consultation.



Colour Coded head  
and hose for easy  
inspection and  
replacing.

## DESIGN AND PERFORMANCE

Product was designed to be very robust, yet economical, and had zero failures to date. Head has been designed to be externally smooth with no dirt traps; the internal surface area is low reducing the area water comes into contact with following advice given by Infection Control experts. Head is not restricted or aerated but delivers a great shower using around 8 liters per min at 2.5 bar pressure and continues to work well down to 0.5 bar pressure. Dependent on previous usage quantities this can reduce water and energy costs while keeping great shower performance.



 shower

**dupal<sup>UK</sup>**



CE

CE

 shower

01 342 844 844  
sales@dupaluk.com  
www.dupaluk.com

Dupal UK Limited  
39 Careys Wood, Smmallfield  
Surrey RH6 9PA, UK

VAT Number: 233 5070 38  
Company Number: 09932632

**dupal**<sup>UK</sup>